

产品技术规格

四开开关



外观颜色:



常规信息

| | | | | | | | |
|----------|--|-----------|--------|--------|-----------|----------|-----------|
| 接线方式: | 强电485 | 弱电485 | 220V强电 | 强电互联互通 | KNX总线 | 无线Zigbee | 弱电干接点 |
| 平台名称: | F平台 | ● | ● | ● | ● | ● | ● |
| 开关类别: | 轻触开关 | ● | ● | ● | ● | ● | ● |
| 系列名称: | V9-ZM | ● | ● | ● | ● | ● | ● |
| 输入电压: | AC220V | DC12V/24V | AC220V | AC220V | DC12V/24V | AC220V | DC12V/24V |
| 阻性负载: | 单路/总路数 ≤1000W | × | ● | ● | ● | ● | × |
| 容性/感性负载: | 单路≤200W | × | ● | ● | ● | ● | × |
| 共阴共阳: | × | × | × | × | × | × | ● |
| 零火线: | ● | × | ● | ● | × | ● | × |
| 通讯端子接口: | ● | ● | × | ● | ● | × | × |
| 第三方RCU: | ● | ● | × | × | KNX | 网关 | × |
| 安装方式: | 国标86安装底盒 | ● | ● | ● | ● | ● | ● |
| 继电器: | 16A | ● | ● | ● | × | ● | × |
| 变背光功能: | ● | ● | ● | ● | ● | ● | ● |
| 触按寿命: | 10万次 | ● | ● | ● | ● | ● | ● |
| 外框支架: | J钢架连支架 (横装、竖装)、Z塑料窄边框、K塑料宽边框、L铝边框、X锌合金边框 | | | | | | |
| 产品特点: | 跑车尾灯式设计、锌合金边框、防眩光设计、多色可选、场景文字定制、变背光、多种接线方案 | | | | | | |

材质

| | | | | | | | |
|-------|----------|---|---|---|---|---|---|
| 表面材质: | 不锈钢锌合金包边 | ● | ● | ● | ● | ● | ● |
| 表面处理: | 纳米电镀工艺 | ● | ● | ● | ● | ● | ● |

尺寸

| | | | | | | | |
|-------|---------------------------|-------|-------|-------|-------|-------|-------|
| 产品尺寸: | W:86 H:86 D:9mm (不含底座) | ● | ● | ● | ● | ● | ● |
| 预埋深度: | ≥45mm | ≥45mm | ≥45mm | ≥45mm | ≥15mm | ≥45mm | ≥15mm |
| 可做连体: | 单 体、二连体、 三连体、四连体; | ● | ● | ● | ● | ● | ● |